

Pallets and Packing Guideline

This guideline is integral part of our terms and conditions of purchase and applies for all orders and deliveries. Any deviations and failures will be recognized as quality defects of delivered goods and registered in our supplier evaluation and rating system.

EURO-pallets:	<u>fabrication:</u>	<u>acc. to UIC-Standard</u>
	dimension:	800 x 1200 mm
	max. weight incl. goods:	950 kg
	max. height incl. pallet:	800 mm

As a basic principle pallets must be in faultless, precise technical condition.

Box packing-mode:

- boxes must be piled up in compound structure
- boxes must be secured against any shifting, using wooden frames, shrink-wrapping or multiply cardboard, flushed with margin of pallets, not overlapping borders of pallet.
- boxes clearly arranged to enable easy quantity-control

Frames:

- accurate fitting to dimension of the pallet
- in faultless and precise technical condition

Mixed pallets:

- remaining quantities and none 1/1 pallet-units not to be mixed-up or packed on several pallets
- generate a min. of mixed pallets

Boxes:

- in accordance with applicable laws and regulations for packing material
- high filling level with min. of unused space
- faultless strong cardboard material

Labels:

- well and properly printed, have to be in line with REYHER label specifications (size, article information, structure, colour)
- any exception, variation or deviation from the specifications has to be approved by REYHER in advance before delivery
- minimum requirements for label data are:
 - DIN / ISO – No.**
 - material / grade**
 - surface**
 - dimension**
 - quantity**
 - batch No.**